

P120-03-005 Issue: E

Date: Oct 2010 Page 1 of 7

PRODUCT NAME: GREASE - KRYTOX® SERIES 240 & LVP

1. Product and Company Identification

Product name: Krytox® 240 Series and LVP fluorinated greases

Synonyms: None

Item Numbers: Krytox® 240AD : U30002525; U30002206

Krytox® 240AB : U30002536; U30002535 Krytox® 240AC : U30002538; U30002537 Krytox® LVP : U300-02-075, U300-02-539

European Contact Details

Edwards, Manor Royal, Crawley West Sussex, RH10 9LW, England E-mail: info@edwardsvacuum.com

General enquiries

UK: +44 (0)1293 528844
France: +(33) 1 47 98 24 01
Germany: +(49) 6420-82-410
Italy: +(39) 0248-4471

US Contact Details

Edwards, Three Highwood Drive, Suite 3-10E, Highwood Office Park, Tewksbury, MA 01876

General enquiries +(1) 978-658-5410

Toll Free: 1-800-848-9800

24 h Emergency telephone number:

Chemtrec: 1-800-424-9300

2. Hazards Identification

EMERGENCY OVERVIEW

This material when properly handled according to good working and hygienic practices is not dangerous to human health and the environment. Product begins to release irritating and toxic fumes above 300 °C/572 °F.

For short and long term exposure effects see Section 11 Toxicological data.

Eye Effects: Excessive exposure may cause irritation, discomfort, excessive lacrimation and blurred

vision.

Skin Effects: Excessive exposure may cause irritation, discomfort and rash.

Ingestion/Oral Effects: Relatively non-toxic.

Inhalation Effects: Low volatility makes inhalation an unlikely hazard in normal use. The thermal

decomposition vapours of fluorinated polymers may cause polymer fume fever with flu

like symptoms in humans, especially when smoking contaminated tobacco.



P120-03-005 Issue: E

Date: Oct 2010 Page 2 of 7

PRODUCT NAME: GREASE - KRYTOX® SERIES 240 & LVP

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

NFPA Hazard codes		HMIS Hazard codes		Rating System	
Health	1	Health	1	0 = No Hazard	
Flammability	0	Flammability	0	1 = Slight Hazard	
Instability	0	Reactivity	0	2 = Moderate Hazard	
				3 = Serious Hazard	
				4 = Severe Hazard	

3. Composition/Information on Ingredients

Ingredient	% Weight	CAS No	Hazard class*	Risk phrase*
Perfluoroalkylether	Krytox® 240 Series: 68-82 Krytox® LVP: 70	60164-51-4	Not applicable	Not applicable
Polytetrafluoroethylene (PTFE)	Krytox® 240 Series: 18-27 Krytox® LVP: 30	9002-84-0	Not applicable	Not applicable

^{*}Hazard class & Risk phrase. These columns are only completed for ingredients which are classified as hazardous under EU Directive No 1272/2008 (as amended) and are present in sufficient concentration to make the overall substance hazardous. In all other situations, the column will be completed as "Not applicable".

4. First Aid Measures

Eyes: Remove contact lenses. Wash/rinse with plenty of water. If irritation persists, consult a

specialist.

Skin: Wash off with soap and water. If irritation persists, seek medical attention.

Ingestion/Oral: Rinse mouth. Drink water as a precaution. Do not induce vomiting without medical advice.

Inhalation: Move to fresh air in case of accidental inhalation of vapours of decomposition products. If

breathing problems occur, a qualified individual should administer oxygen or artificial

respiration as indicated. Seek immediate medical attention.

Other Information: Never give anything by mouth to an unconscious person. If substantial quantities are ingested,

seek medical attention.



P120-03-005 Issue: E

Date: Oct 2010 Page 3 of 7

PRODUCT NAME: GREASE - KRYTOX® SERIES 240 & LVP

5. Fire Fighting Measures

Extinguishing Media: The products do not burn. Select extinguishing media to suit other material(s)

involved.

Fire and Explosion Hazard: Possible risk due to irritation and toxic affects of thermal combustion products at

temperatures above 300 °C/572 °F. Fire may produce toxic fluorine compounds

including hydrogen fluoride, phosgene, and perfluoroolefins.

Special Protective Equipment

for Fire Fighters:

Fire fighters should wear a self-contained breathing apparatus (SCBA) which meets appropriate standards operated in positive pressure mode. Skin protection

should be worn to protect from thermal combustion products.

For Flammability Properties - see Section 9.

6. Accidental Release Measures

In the event of spillage:

• Wear personal protective clothing (see Section 8 Exposure Controls and Personal Protection).

• Recover released product and collect in a suitable container for reuse or disposal. Wash area to prevent slip hazard.

• Avoid discharge into sewage systems, surface or underground waters and the soil.

7. Handling and Storage

Handling: Avoid temperatures above 300 °C/572 °F without adequate ventilation. Avoid contact with

eyes and skin.

Do not carry cigarettes or cigars or smoke in areas where this product is being used or stored. Greasy hands may contaminate tobacco products. Smoking contaminated products may cause

polymer fume fever. Wash thoroughly after handling and before meals and breaks.

Storage: Keep containers tightly closed and store in dry, cool well-ventilated areas. No special

restrictions on storage with other products. Store in glass or polythene containers.



P120-03-005 Issue: E

Date: Oct 2010 Page 4 of 7

PRODUCT NAME: GREASE - KRYTOX® SERIES 240 & LVP

8. Exposure Controls/Personal Protection

Exposure Limits:

Ingredient	ACGIH - TLV -	OSHA - PEL	Occupational Exposure Limits EH40 (UK)
None	Not Applicable	Not Applicable	Not Applicable

Personal Protection:

Engineering Measures: None required under normal conditions of use. Heat only in areas with

appropriate exhaust ventilation.

Respiratory Protection: None required under normal conditions of use. Wear suitable self-contained

breathing apparatus if heating above 300 °C/572 °F.

Hand/Skin Protection: Wear impervious gloves.

Eye/Face Protection: Use safety glasses.

Hygiene Measures: Wash hands before taking breaks and immediately after handling the product.

Keep away from tobacco products.

Other/General Protection: None.

9. Physical and Chemical Properties

Appearance and Odour	Solid white odourless paste	Boiling point	No data available	°C/°F
pH (as supplied)	Neutral	Melting point	320 / 608	°C/°F
Solubility in Water	Insoluble	Auto Ignition	Not applicable	°C/°F
Volatile Content by Volume	No data available	Flash Point	Does not flash	°C/°F
Specific Gravity	1.89 - 1.93 @ 25 °C / 77 °F			
Vapour Pressure (mbar)	No data available	Vapour Pressure (Torr)	No data available	

10. Stability and Reactivity

Stability: Stable.

Material/Conditions to Avoid: No materials to be specifically avoided. Avoid heating to above 300 °C/572 °F.

Hazardous Decomposition: Vapours which may irritate the respiratory system may be released above

300 °C/572 °F. Thermal decomposition will produce toxic fluorine compounds.

Hazardous Polymerisation: Will not occur.



P120-03-005 Issue: E

Date: Oct 2010 Page 5 of 7

PRODUCT NAME: GREASE - KRYTOX® SERIES 240 & LVP

11. Toxicological Information

For a comprehensive description for the various toxicological (health) effects which may arise if the user comes into contact with the substance or preparation refer to Section 2 Hazards Identification.

Animal data:

ALD value: >11000 mg/kg (rat).

ALC value: No specific data available.

Note: This data is for perfluoroalkylether.

Note: ALD/ALC = Average lethal dose/ average lethal concentration.

Carcinogenicity:

No information available.

Toxicity information for PTFE decomposition products:

Ingestion: LD50 >25000 mg/kg.

Inhalation: PTFE decomposition products vary widely in toxicity in experimental animals. Four hour LC50s (inhalation)

for decomposition products range from 0.76 ppm (perfluoroisobutane) to 40,000 ppm

(tetrafluoroethylene monomer). Workers exposed to PTFE fumes produced at 350-380 °C (temperatures associated with liberation of hexafluoroethane, perfluoroisobutylene, and octafluorocyclobutene) exhibited symptoms consistent with polymer fume fever at workplace air concentrations of 3.5 mg/m³

compounds containing fluorine.

Chronic: Repeated episodes of polymer fume fever may damage the lungs.

12. Ecological Information

Toxicity (perfluoroalkylether):

LC50 /96 hr /Oncorhynchus mykiss (rainbow trout) : > 1 000 mg/l.

Aguatic toxicity is unlikely due to low solubility.

Static test /EC50 /48 hr /Daphnia magna (Water flea): > 1 000 mg/l.

13. Disposal Considerations

If recycling is not practicable, dispose of residues, unused grease and contaminated packaging in compliance with local and national regulations.



P120-03-005 Issue: E

Date: Oct 2010 Page 6 of 7

PRODUCT NAME: GREASE - KRYTOX® SERIES 240 & LVP

14. Transport Information

This product is not classified as dangerous under transport regulations.

PARAMETER	EUROPEAN	CANADIAN TDG	UNITED STATES DOT
Proper Shipping Name	Not applicable	Not applicable	Not applicable
Hazard Class	Not applicable	Not applicable	Not applicable
Identification Number	Not applicable	Not applicable	Not applicable
Shipping Label	Not applicable	Not applicable	Not applicable

15. Regulatory Information

European Regulatory Information

This product has been classified in accordance with EU Regulation No 1272/2008 (as amended) on the Classification, Labelling and Packaging of Substances and Mixtures.

Classified as dangerous to supply: No.

Risk Phrases : Not applicable.
Safety Phrases : Not applicable.

Symbols: None.

United States Regulatory Information

All ingredients contained in this product are included on the EPA TSCA Chemical Substance Inventory.

SARA TITLE III - SECTION 313 SUPPLIER NOTIFICATION:

This product does not contain toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA of 1986 and 40 CFR Part 372.

California Proposition 65: This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive toxicity.

Canadian Regulatory Information

WHMIS Classification: D2B.

All ingredients contained in this product are included on the Canadian DSL.



P120-03-005 Issue: E

Date: Oct 2010 Page 7 of 7

PRODUCT NAME: GREASE - KRYTOX® SERIES 240 & LVP

16. Other Information

This MSDS is compiled in accordance with ANSI Z400.1 and Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Sources of information for this data sheet:

- DuPont Safety Data Sheet for "Krytox® Fluorinated Grease". Reference: 150000001170. Version 3.0 Revision Date 17.12.2009.
- National Library of Medicine (NLM) electronic databases (HSDB, RTECS, CHEMID, Toxline).

Glossary:

ACGIH - American Conference of Governmental Industrial Hygienists; ALC - Average Lethal Concentration; ALD - Average Lethal Dose; ANSI - American National Standards Institute; Canadian TDG - Canadian Transportation of Dangerous Goods; CAS - Chemical Abstracts Service; CHEMID - Chemical Identification Database; Chemtrec - Chemical Transportation Emergency Center (US); DSL - Domestic Substances List; EC - Equivalent Concentration; EH40 (UK) - HSE Guidance Note EH40 Occupational exposure limits; EPA - Environmental Protection Agency; EPCRA - Emergency Planning and Community Right-To-Know Act; HMIS - Hazardous Material Information Service; HSDB - Hazardous Substances Data Base; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; NLM - National Library of Medicine; OSHA - Occupational Safety and Health Administration, US department of Labour; PEL - Permissible exposure limit; RTECS - Registry of Toxic Effects of Chemical Substances; SARA (Title III) - Superfund Amendments and Reauthorization Act; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self-Contained Breathing Apparatus; STEL - Short Term Exposure Limit; TLV - threshold limit value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-Weighted Average; US DOT - US Department of Transportation; WHMIS - Workplace Hazardous Materials Information System.

Revisions:

October 2010 - Data Sheet updated to reflect the latest regulatory and supplier safety information.

Although the information and recommendations in this data sheet are to the best of our knowledge correct, it is recommended that you make your own determination of the material's suitability for your purpose before you use it. The information contained in this data sheet has been reproduced from the manufacturers data; the accuracy of this information is the responsibility of the manufacturer. Edwards accept no responsibility for damage of any nature resulting from the use of, or the reliance upon, this data sheet.