

P120-20-140 Issue: C Date: Aug 10

Page 1 of 6

PRODUCT NAME: EXCHANGE RESIN

1. Product and Company Identification

Exchange Resin Product name:

Synonyms: None

Item Numbers: E427-10-800, E427-11-100

European Contact Details

Edwards, Manor Royal, Crawley West Sussex, RH10 9LW, England E-mail: info@edwardsvacuum.com

General enquiries

UK: +44 (0)1293 528844 France: +(33) 1 47 98 24 01 Germany: +(49) 6420-82-410 Italy: +(39) 0248-4471

US Contact Details

Edwards, Three Highwood Drive, Suite 3-10E, Highwood Office Park, Tewksbury, MA 01876

General enquiries +(1) 978-658-5410

Toll Free: 1-800-848-9800

24 h Emergency telephone number:

Chemtrec: 1-800-424-9300

2. Hazards Identification

EMERGENCY OVERVIEW

This dried resin product may cause eye or skin irritation, but when properly handled according to good working and hygienic practices is not dangerous to human health. Combustion products may include monomers, organics, amines, carbon oxides, nitrogen oxides and sulphur oxides.

For short and long term exposure effects see Section 11 Toxicological data.

Eye Effects: May cause irritation.

Skin Effects: May cause mild irritation.

Ingestion/Oral Effects: Ingestion of large amounts may cause gastrointestinal irritation.

Inhalation Effects: Inhalation of high concentrations of dust may cause irritation.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

NFPA Hazard codes		HMIS Hazard codes		Rating System	
Health	2	Health	2	0 = No Hazard	
Flammability	1	Flammability	1	1 = Slight Hazard 2 = Moderate Hazard	
Instability	1	Reactivity	1		
			3 = Serious Hazard		
				4 = Severe Hazard	



P120-20-140 Issue: C Date: Aug 10

Page 2 of 6

PRODUCT NAME: EXCHANGE RESIN

3. Composition/Information on Ingredients

Ingredient	% Weight	CAS No	Hazard class*	Risk phrase*
Polystyrene sulphonic acid	20-30	69011-20-7	Not applicable	R36
Polyvinyl benzyl trimethyl ammonium hydroxide	20-30	69011-18-3	Not applicable	R36
Moisture	40-65	7732-18-5	Not applicable	Not applicable

^{*}Hazard class & Risk phrase. These columns are only completed for ingredients which are classified as hazardous under EU Directive No 1272/2008 (as amended) and are present in sufficient concentration to make the overall substance hazardous. In all other situations, the column will be completed as "Not applicable".

4. First Aid Measures

Immediately wash out with plenty of water for at least 15 minutes. If irritation persists, seek Eyes:

medical attention.

Skin: Remove contaminated clothing. Remove any particles from skin, and wash with soap and

water.

Wash out mouth with water and give two glasses of water to drink. Seek immediate medical Ingestion/Oral:

attention. Do not induce vomiting! Never give anything by mouth to an unconscious person!

Inhalation: If high concentrations of dust are inhaled, remove to fresh air. Seek medical attention.

Other Information: None.

5. Fire Fighting Measures

Extinguishing Media: Foam, dry powder, water spray.

Fire and Explosion Hazard: Combustion products may include monomers, residual organics, amines, carbon

oxides, nitrogen oxides and sulphur oxides. Explosion may occur if the material

comes into contact with nitric acid or strong oxidizers.

Special Protective Equipment

for Fire Fighters:

Fire fighters should wear a self-contained breathing apparatus (SCBA) and full

protective gear.

For Flammability Properties - see Section 9.

6. Accidental Release Measures

Isolate the area of the spill. Wear appropriate protective equipment (See Section 8).

Spilled material may cause floors to be slippery. Take care to avoid falls.

Sweep up the spilled material and transfer to plastic containers for recovery or disposal: see Section 13.

Take measures to prevent run off water (from the spill) from entering drains, sewers or watercourses. If polluted water reaches drainage systems or water courses, immediately inform the appropriate authorities.



P120-20-140 Issue: C Date: Aug 10

Page 3 of 6

PRODUCT NAME: EXCHANGE RESIN

7. Handling and Storage

Handling: Wear suitable protective equipment (see Section 8). No other special measures are required.

Note, however, that static charges may accumulate in the material. Prevent contact with

materials sensitive to static discharge.

Storage: Store in the original container, in a well ventilated place, between 0 and 40 °C

> (32 and 104 °F). May evolve hazardous amines above 50 °C (122 °F). Avoid freezing. Avoid dehydration: when rehydrated, the volume of the material may increase and rupture its

packaging.

8. Exposure Controls/Personal Protection

Exposure Limits:

Ingredient	ACGIH - TLV -	OSHA - PEL	Occupational Exposure Limits EH40 (UK)
None	Not applicable	Not applicable	Not applicable

Personal Protection:

Engineering Measures: No special ventilation is required.

Respiratory Protection: No respiratory protection is required for normal use.

Hand/Skin Protection: Wear suitable gloves and protective overalls.

Eye/Face Protection: Wear safety goggles. Ensure an eyewash facility is available.

Hygiene Measures: Practice good workplace hygiene. Do not eat or smoke when handling. Wash

thoroughly after handling, before meals, breaks, and leaving the work area.

Other/General Protection: None.

9. Physical and Chemical Properties

Appearance and Odour	White/cream/amber/brown beads, odourless	Boiling point	Not applicable	°C/°F
pH (as supplied)	No data available	Freezing Point	Not applicable	°C/°F
Solubility in Water	Insoluble	Auto Ignition	No data available	°C/°F
Volatile Content by Volume	Not applicable	Flash Point	Not applicable	°C/°F
Specific Gravity	1.05 to 1.28 (in water)			
Vapour Pressure (mbar)	No data available	Vapour Pressure (Torr)	No data available	



P120-20-140 Issue: C Date: Aug 10 Page 4 of 6

PRODUCT NAME: EXCHANGE RESIN

10. Stability and Reactivity

Stability: Stable under normal conditions of use. Anion exchangers may give off amine

vapours at temperatures > 50 °C (122 °F).

Material/Conditions to Avoid: Avoid contact with nitric acid and strong oxidizers, due to the risk of explosion.

Hazardous Decomposition: Combustion products may include monomers, residual organics, amines, carbon

oxides, nitrogen oxides and sulphur oxides. Dried resins start to burn at

230 °C (446 °F).

Hazardous Polymerisation: Will not occur.

11. Toxicological Information

For a comprehensive description of the various toxicological (health) effects which may arise if the user comes into contact with the substance or preparation, refer to Section 2 Hazards Identification.

Acute toxicity:

No evidence of acute toxicity.

Carcinogenicity:

No known carcinogenic effects.

Teratogenicity

No evidence of reproductive effects.

Mutagenicity

No evidence of mutagenic effects.

12. Ecological Information

The material has low ecotoxicity because it is virtually insoluble in water. The material is not readily biodegradable. If it enters a watercourse, the material may change the pH of the water. Inform the appropriate authorities of major spills.

13. Disposal Considerations

The material as supplied is classified as hazardous waste.

Used material fully loaded with non-hazardous ions is classified as a non-hazardous special waste. Used material loaded with hazardous ions is classified as a special hazardous waste.

Dispose of new/used material in accordance with its classification and with all local, regional and national disposal safety regulations.

- EU number for exhausted or saturated ion exchange resins used in chemical surface treatment and coating of metals is 1101 16.
- EU number for exhausted or saturated ion exchange resins used for the preparation of drinking water or water for industrial use is 19 09 05.



P120-20-140 Issue: C Date: Aug 10 Page 5 of 6

PRODUCT NAME: EXCHANGE RESIN

- EU number for exhausted or saturated ion exchange resins used in waste water treatment plants not otherwise specified is 19 08 06.
- In UK, surplus product should be declared a 'Special Waste'. Refer to the 'Control of Pollution (Special Waste) Regulations 1980 SI 1709'.

14. Transport Information

This material as supplied is not classified as dangerous under transport regulations.

PARAMETER	EUROPEAN	CANADIAN TDG	UNITED STATES DOT
Proper Shipping Name	Not applicable	Not applicable	Not applicable
Hazard Class	Not applicable	Not applicable	Not applicable
Identification Number	Not applicable	Not applicable	Not applicable
Shipping Label	Not applicable	Not applicable	Not applicable

Used material contaminated by hazardous ions is subject to transport regulations for hazardous wastes.

15. Regulatory Information

European Regulatory Information

This product has been classified in accordance with EU Regulation No 1272/2008 (as amended) on the Classification, Labelling and Packaging of Substances and Mixtures.

Classified as dangerous to supply: Yes.

Risk Phrases: R36 - Irritating to eyes.

Safety Phrases: S26 - In case of contact with eyes, rinse immediately with plenty of water and

and seek medical advice.

S39 - Wear eye/face protection.

Symbols: Xi - Irritant.

United States Regulatory Information

All materials contained in this product are listed on the U.S. Toxic Substances Control Act (TSCA).

SARA TITLE III - SECTION 313 SUPPLIER NOTIFICATION:

This product does not contain toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act (EPCRA) of 1986 and 40 CFR Part 372.

California Proposition 65: This product does not contain chemicals known to the State of California to cause cancer or reproductive toxicity.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Canadian Regulatory Information

WHMIS Classification: D2B.

All ingredients in this product are included in the Canadian DSL.



P120-20-140 Issue: C Date: Aug 10 Page 6 of 6

PRODUCT NAME: EXCHANGE RESIN

16. Other Information

This MSDS is compiled in accordance with ANSI Z400.1 and Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Sources of information for this data sheet:

- Purolite International Material Safety Data Sheet Number 18. Revision No. 00. First issue date: 08 September 2003.
- Purolite Safety Data Sheet for Purolite® NRW37. Revision date: 18 January 2010.

Glossary:

ACGIH - American Conference of Governmental Industrial Hygienists; ANSI - American National Standards Institute; Canadian TDG - Canadian Transportation of Dangerous Goods; CAS - Chemical Abstracts Service; Chemtrec - Chemical Transportation Emergency Center (US); DSL - Domestic Substances List; EH40 (UK) - HSE Guidance Note EH40 Occupational exposure limits; EPCRA - Emergency Planning and Community Right-to-Know Act; HMIS - Hazardous Material Information Service; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OSHA - Occupational Safety and Health Administration, US department of Labour; PEL - Permissible exposure limit; SARA (Title III) - Superfund Amendments and Reauthorization Act; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self-Contained Breathing Apparatus; TLV - threshold limit value; TSCA - Toxic Substances Control Act Public Law 94-469; US DOT - US Department of Transportation; WHMIS - Workplace Hazardous Materials Information System; WGK - Wassergefährdungsklasse (German Water Hazard Classification).

Revisions:

August 2010 - Data Sheet updated to reflect the latest regulatory and supplier safety information.

Although the information and recommendations in this data sheet are to the best of our knowledge correct, it is recommended that you make your own determination of the material's suitability for your purpose before you use it. The information contained in this data sheet has been reproduced from the manufacturers data; the accuracy of this information is the responsibility of the manufacturer. Edwards accept no responsibility for damage of any nature resulting from the use of, or the reliance upon, this data sheet.